



Technical Datasheet pL-Powerbox

Do you want to use your industrial PC for mobile applications? Our battery box is the compact and portable power supply for your mobile application in this case. The battery box stands out with its low weight as well as the longevity in the battery technology.

Battery box for industrial PCs

The compatibility of the pL battery box makes it the ideal battery supplement to our industrial PCs.

- PELI Case housing
- Water-tight, break-resistant, dust-tight
- Plastic housing with pressure compensation valve

We will gladly advise you individually.

YOUR MOBILE ENERGY SOURCE

DIMENSIONS (HEIGHT)	124 mm		
DIMENSIONS (WIDTH)	272 mm		
DIMENSIONS (DEPTH)	248 mm		Anoneoroud
WEIGHT	6,250 g		
AMBIENCE TEMPERATURE (CHARGING)	0°C-+40°	C	
AMBIENCE TEMPERATURE (DISCHARGING)	-10°C - +60	°C	- On-site visit
AMBIENCE TEMPERATURE (WAREHOUSE)	25°C		- Consulting - Order management
CAPACITY	31 Ah		- Development - Production
PERFORMANCE	815 Wh		- Assembly
NOMINAL	25.9 V		
VOLTAGE	approx. 19	6 V	
DEEP DISCHARGE DEACTIVATION	29.4 V		
CHARGING TIME	approx. 8 h at complet	nours ely discharged battery	
SELF-DISCHARGE	< 0.1%/day		
CHARGING METHOD	CC/CV		Ó
CHARGE CURRENT	4 A		the set
BATTERY TYPE	Li-Ion		
MONITORING	BMS (battery management system)		

